Printing date 12.09.2018 Revision: 12.09.2018

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: MR ®Lobosil Silicon Lubricant Spray
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages

F Formulation or re-packing

IS Use at industrial Sites

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category

PC14 Metal surface treatment products

PC24 Lubricants, greases, release products

Process category

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

· Article category

AC7 Metal articles

AC13 Plastic articles

- · Application of the substance / the mixture Sliding and parting agent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MR® Chemie GmbH

Nordstr. 61-63

59427 Unna (Germany)

Tel. +49 (0)2303 95151 0

Fax: +49 (0)2303 95151 10

post@mr-chemie.de

www.mr-chemie.de

· Further information obtainable from:

MR Chemie GmbH. Dep. safety data sheets. Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de

· 1.4 Emergency telephone number:

24h- Emergency Contact Phone Number For Chemical Emergency, Spill, Leak, Fire, Exposure or

Accident (WISAG FMO Cargo Service GmbH & CO.KG)

Call Day or Night within USA and Canada: 1 800 424 9300

Outside USA and Canada: 001 703 527 3887

In-Country Emergency Number for:

Germany: 0800-181-7059

China: 4001 204937 (Mandarin)
Hong Kong: 800 968 793 (Cantonese)
India: 000 800 100 7141 (Hindi)
South Africa: 0 800 983 611 (English)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The mixture is classified according to Regulation (EC) No 1272/2008 according to the most recent ATP.



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. (Contd. on page 2)

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: MR ®Lobosil Silicon Lubricant Spray

(Contd. of page 1)

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 ℃/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	butane (containing \leq 0,1 % butadiene (203-450-8)) Flam. Gas 1, H220 Press. Gas (Comp.), H280	40 - 50%
	propane Flam. Gas 1, H220 Press. Gas (Comp.), H280	40 - 50%
	2-Propanol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	1 - 5%

- · Propellant: Propane-Butane
- · Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Seek medical advice if symptoms occurs or in cases of doubt.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: MR ®Lobosil Silicon Lubricant Spray

(Contd. of page 2)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Not relevant aerosol can.
- · 4.2 Most important symptoms and effects, both acute and delayed Dizziness
- Information for doctor:

Grease with skin-cream to restore fat film in order to prevent skin inflammation.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

organic cracked products

Steams are heavier than air and spread at the soil.

In case of fire, the following can be released:

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, e.g. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Do not store together with fire-promoting or self-ignitory products.

· Further information about storage conditions: Protect from heat and direct sunlight.

(Contd. on page 4)

Revision: 12.09.2018 Printing date 12.09.2018

Trade name: MR ®Lobosil Silicon Lubricant Spray

(Contd. of page 3)

- · Recommended storage temperature: 5 45 °C, 41 113 °F
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

Ingredients with lim	nit values that require monitoring at the workplace:
74-98-6 propane	
AGW (Germany)	Long-term value: 1800 mg/m³, 1000 ppm 4(II);DFG
106-97-8 butane (co	ontaining ≤ 0,1 % butadiene (203-450-8))
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
AGW (Germany)	Long-term value: 2400 mg/m³, 1000 ppm 4(II);DFG
67-63-0 2-Propanol	
WEL (Great Britain)	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm
AGW (Germany)	Long-term value: 500 mg/m³, 200 ppm 2(II);DFG, Y

DNELS

67-63-0 2-	•
Dermal	Long-term - systemic effects, worker 888 mg/kg bw/day (worker)
Inhalative	Long-term - systemic effects, worker 500 mg/m³ (worker)

· PNECs

67-63-0 2-Propanol

Aquatic compartment, freshwater	140.9 mg/L (freshwater)
Aquatic compartment - marine water	140.9 mg/L (marine water)
Aquatic compartment- sediment in freshwater	552 mg/kg sed dw (sediment fresh water)
Aquatic compartment sediment in marine water	552 mg/kg sed dw (sediment marine water)
Terrestrial compartment - soil	28 mg/kg dw (soil)
Sewage treatment plant	2,251 mg/L (sewage treatment plant)
Oral secondary poisoning	160 mg/kg food (food secundary poisoning)

· Ingredients with biological limit values:

67-63-0 2-Propanol

BGW (Germany) 25 mg/l

Untersuchungsmaterial: Vollblut

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: Aceton

25 mg/l

Untersuchungsmaterial: Urin

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: Aceton

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.

(Contd. on page 5)

(Contd. of page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: MR ®Lobosil Silicon Lubricant Spray

· Respiratory protection:

Filter AX

For good ventilation provide, this can be achieved by local or space exhaust. If the concentration lies over the job limit values, then, a certified respirator suitable for this purpose must be used.

Protection of hands:

Check the permeability prior to each anewed use of the glove.

For the protection against chemicals in areas with heightened risk of injury (mechanical hazard) no recommendation for a suitable glove material can be given.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Rubber gloves

Recommended thickness of the material: > 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 6 Supplier for suitable protection gloves:

ASD ArbeitsSicherheit Dortmund

Torstr. 101 - 37355 Niederorschel OT Rüdigershagen

Tel.: 02301 / 919543 - Fax: 02301 / 9453893

E-Mail: m.schnellhardt@t-online.de - http://www.arbeitssicherheitdortmund.de

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: With danger of the eye contact closing eye protector.
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information	on on basic	physica	l and c	hemica	properties
-------------------	-------------	---------	---------	--------	------------

· General Information

· Appearance:

Form: Aerosol
Colour: Whitish
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: -80 °C

Basis: propellant

· Flammability (solid, gas): Not applicable.

· **Ignition temperature:** Not determined - aerosol.

• Decomposition temperature: Not determined.

• **Auto-ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 6)

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: MR ®Lobosil Silicon Lubricant Spray

	(Contd. of page
Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.9 Vol %
Vapour pressure at 20 ℃:	8,300 hPa
•	Basis: propellant
Density at 20 ℃:	0.888 g/cm ³
•	Basis: active substance
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organic solvents:	94.0 %
VOC (EU)	94.00 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

Danger of bursting of the aerosol can during overheating

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
106-97-8	106-97-8 butane (containing ≤ 0,1 % butadiene (203-450-8))		
Inhalative	Inhalative LC50/4 h 658 mg/l (rat)		
67-63-0 2-	67-63-0 2-Propanol		
Oral	LD50	5,045 mg/kg (rat)	
Dermal	LD50	12,800 mg/kg (rbt)	
	LC50/4 h	30 mg/l (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: MR ®Lobosil Silicon Lubricant Spray

(Contd. of page 6)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1: weakly water-endangering
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Eliminate the pure, unchanged substance in accordance with local regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste disposal key:

For this product no waste key number can be specified, because only the intended purpose permits an allocation. The waste key number is to be specified in arrangement with the regional waste disposal.

The indications for Waste key reflect the pure unmodified product and are only a recommendation.

· Europea	· European waste catalogue	
07 06 99	07 06 99 wastes not otherwise specified	
15 01 04	metallic packaging	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
· ADR	1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	
		(Contd. on page

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: MR ®Lobosil Silicon Lubricant Spray

	(Contd. of page
14.3 Transport hazard class(es)	
ADR	
Class Label	2 5F Gases. 2.1
	Δ.1
IMDG, IATA	
2	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Na
Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler):	Warning: Gases.
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capaci of 1 litre: Category A. For AEROSOLS with
	capacity above 1 litre: Category B. For WAST
Segregation Code	AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity
Segregation Code	1 litre: Segregation as for class 9. Stow "separate
	from" class 1 except for division 1.4. Fo
	AEROSOLS with a capacity above 1 litro Segregation as for the appropriate subdivision
	class 2. For WASTE AEROSOLS: Segregation a
	for the appropriate subdivision of class 2.
14.7 Transport in bulk according to An of Marpol and the IBC Code	nex II Not applicable.
Transport/Additional information:	rect applicable.
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
Transport category	Not permitted as Excepted Quantity 2
Tunnel restriction code	D
IMDG	-
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
	(Contd. on page

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: MR ®Lobosil Silicon Lubricant Spray

(Contd. of page 8)

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Waterhazard class: Water hazard class 1: slightly hazardous for water.
- · VOC (EU) 834.7 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The data in this safety data sheet are based on our knowledge at the time of the revision. The information should give you reference points for a safe handling of the product specified in this safety data sheet. The data are not transferable to other products. If the product specified in this safety data sheet is mixed or processed with other materials, the data cannot be transferred without examination.

· Relevant phrases

The wording of the listed risk phrases are those of the individual raw materials.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

· Recommended restriction of use

Existing national and local laws concerning chemicals are to be considered.

Department issuing SDS:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38

· Contact:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (Éuropean Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

(Contd. on page 10)

Page 10/10

(Contd. of page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: MR ®Lobosil Silicon Lubricant Spray

Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.